



Seismic™ 10

Design	built-in Ultra-Class-D™ amplifier, single high-excursion driver, dual passive radiators,
Amplifier High Current Discrete Output	4500 watts Dynamic Peak / 1500 watts RMS Sustained,
Amplifier Design Features	Auto-On/Off, Trigger-On/Off, soft clipping, thermal protection, electrical shorting protection,
Bass Driver	
Passive Radiator	Dual 229-mm (9 in) balanced plane high-velocity passive radiators,
Finishes	Black Ash with Gloss Top,
Low Frequency Extension	21 Hz (DIN)
Subwoofer Cutoff Frequency	Variable 35 Hz - 150 Hz
Subwoofer Contour	-
Sub./Sat. Phase Alignment	-
Line Level Input	RCA (S/E) or Balanced-XLR. From Sub-Out / LFE-Out of receiver / processor or other line-level source
Line Level Input Impedance	RCA:25k ohms; XLR:20k ohms
Line-Level High-Pass Output	-
Line-Level High-Pass Output Roll-Off	-
Speaker Level Input	
Speaker-Level Input Sensitivity	
Internal Volume	19.7 L / 0.69 cu ft
Height,Width,Depth	33 cm x 31 cm x 31 cm 13 in x 12-1/4 in x 12-1/4 in
Weight	49lb / 22.20kg